



ELECTRIC PALLET TRUCKS



	16ET-7	18ET-7	20ET-7	22ET-7	22EP6-7	22EP9-7
• Load capacity	1600 kg (3200 lb)	1800 kg (3600 lb)	2000 kg (4000 lb)	2200 kg (4400 lb)	2200 kg (4400 lb)	2200 kg (4400 lb)
• Lifting height (max.)	210 mm (8,3 in)	210 mm (8,3 in)	210 mm (8,3 in)	210 mm (8,3 in)	210 mm (8,3 in)	210 mm (8,3 in)
• Turning radius	1375 mm (54,1 in)	1484 mm (58,4 in)	1484 mm (58,4 in)	1564 mm (61,6 in)	2070 mm (81,5 in)	2070 mm (81,5 in)
• Battery capacity (nominal)	24 V / 150 Ah	24 V / 180 Ah	24 V / 180 Ah	24 V / 270 Ah	24 V / 270 Ah	24 V / 270 Ah
• Travel speed (unloaded)	6 km/h (3,7 mph)	6 km/h (3,7 mph)	6 km/h (3,7 mph)	6 km/h (3,7 mph)	6 km/h (3,7 mph)	9 km/h (5,6 mph)
					Foldable Platform	Foldable Platform & Body-side-protectors



ELECTRIC STACKERS



	10ES-7	14ES-7	10LS-7	12LS-7	14LS-7
• Load capacity	1000 kg (2000 lb)	1400 kg (2800 lb)	1000 kg (2000 lb)	1200 kg (2400 lb)	1400 kg (2800 lb)
• Lifting height (max.)	2740 mm (107,9 in)	900 mm (35,4 in)	4340 mm (170,9 in)	4340 mm (170,9 in)	4340 mm (170,9 in)
• Turning radius	1346 mm (53,0 in)	1385 mm (54,5 in)	1400 mm (55,1 in)	1400 mm (55,1 in)	1410 mm (55,5 in)
• Battery capacity (nominal)	24 V / 85 Ah	24 V / 85 Ah	24 V / 180-240 Ah	24 V / 180-240 Ah	24 V / 180-240 Ah
• Travel speed (unloaded)	4,5 km/h (2,8 mph)	5 km/h (3,1 mph)	5 km/h (3,1 mph)	5 km/h (3,1 mph)	5 km/h (3,1 mph)
	Range of attachments				



	14MS-7	14MSL-7	16MS-7	16MSL-7	16HS-7	16HSL-7	20HS-7	20HSL-7
• Load capacity	1400 kg (2800 lb)	1400 kg (2800 lb)	1600 kg (3200 lb)	1600 kg (3200 lb)	1600 kg (3200 lb)	1600 kg (3200 lb)	2000 kg (4000 lb)	2000 kg (4000 lb)
• Lifting height (max.)	4855 mm (191,1 in)	4856 mm (191,2 in)	4855 mm (191,1 in)	4856 mm (191,2 in)	5455 mm (214,8 in)	5460 mm (215,0 in)	5455 mm (214,8 in)	5460 mm (215,0 in)
• Turning radius	1400 mm (55,1 in)	1400 mm (55,1 in)	1400 mm (55,1 in)	1400 mm (55,1 in)	1591 mm (62,6 in)	1837 mm (72,3 in)	1591 mm (62,6 in)	1837 mm (72,3 in)
• Battery capacity (nominal)	24 V / 160-250 Ah	24 V / 160-250 Ah	24 V / 160-250 Ah	24 V / 160-250 Ah	24 V / 270-375 Ah	24 V / 270-375 Ah	24 V / 270-375 Ah	24 V / 270-375 Ah
• Travel speed (unloaded)	6 km/h (3,7 mph)	6 km/h (3,7 mph)	6 km/h (3,7 mph)	6 km/h (3,7 mph)	6 km/h (3,7 mph)	6 km/h (3,7 mph)	6 km/h (3,7 mph)	6 km/h (3,7 mph)
		Initial lift		Initial lift		Initial lift		Initial lift



TOW TRUCKS



	20DS-7	20DSP-7	40T-7	15P-7
• Load capacity	2000 kg	2000 kg	4000 kg (8000 lb)	1500 kg (3000 lb)
• Lifting height (max.)	2175 mm (85,6 in)	2175 mm (85,6 in)	/	/
• Turning radius	1691 mm (66,6 in)	1867 mm (73,5 in)	/	/
• Battery capacity (nominal)	24 V / 270-360 Ah	24 V / 270-360 Ah	1565 mm (61,6 in)	2065 mm (81,3 in)
• Travel speed (unloaded)	5,6 km/h (3,5 mph)	5,6 km/h (3,5 mph)	48 V / 280 Ah	48 V / 280 Ah
		foldable platform	10,0 km/hr (6,2 mph)	10,0 km/hr (6,2 mph)

WORK OR *pleasure?*

Enabling machine operators to take pleasure in their work, is our number one priority.

Therefore, Hyundai developed a complete line of precise and performant products.

You see, we invest to offer you quality solutions, with more than just the machine in mind.

Hyundai strives for continuous product improvement and outstanding service, to build a better future.



HYUNDAI HEAVY INDUSTRIES EUROPE MATERIAL HANDLING

European Operation
HYUNDAI HEAVY INDUSTRIES EUROPE N. V.
VOSSENDAAL 11, 2440 GEEL, BELGIUM
TEL : 32-14-56-2200 FAX : 32-14-59-3403
www.hyundai.eu

Standard and optional equipment may vary. Contact your Hyundai dealer for more information. The machine shown may vary according to International standards. Materials and specifications are subject to change without notice.

Distributed by

2009.09

EN - www.hyundai.eu



www.hyundai.eu

Hyundai Material Handling

PRODUCT OVERVIEW



* Photo may include optional equipment.





DIESEL FORKLIFTS



	15D-7E	18D-7E	20DA-7E	20D-7E	25D-7E	30D-7E	33D-7E	35DS-7E	40DS-7E	45DS-7E	50DA-7E	50DS-7E	60DS-7E	70DS-7E
• Load capacity	1500 kg (3000 lb)	1750 kg (3500 lb)	2000 kg (4000 lb)	2000 kg (4000 lb)	2500 kg (5000 lb)	3000 kg (6000 lb)	3300 kg (6600 lb)	3500 kg (7000 lb)	4000 kg (8000 lb)	4500 kg (9000 lb)	5000 kg (10000 lb)	5000 kg (10000 lb)	6000 kg (12000 lb)	7000 kg (14000 lb)
• Load center	500 mm (19,7 in)	500 mm (19,7 in)	500 mm (19,7 in)	500 mm (19,7 in)	500 mm (19,7 in)	500 mm (19,7 in)	500 mm (19,7 in)	600 mm (23,6 in)	600 mm (23,6 in)	600 mm (23,6 in)	600 mm (23,6 in)	600 mm (23,6 in)	600 mm (23,6 in)	600 mm (23,6 in)
• Lifting height (max.)	7035 mm (277 in)	7035 mm (277 in)	7040 mm (277 in)	7000 mm (275,6 in)	7000 mm (275,6 in)	7000 mm (275,6 in)	7000 mm (275,6 in)	6030 mm (237,4 in)	6030 mm (237,4 in)	6030 mm (237,4 in)	5972 mm (235,1 in)	6060 mm (238,6 in)	6060 mm (238,6 in)	6060 mm (238,6 in)
• Engine	Kubota V2203	Kubota V2203	Kubota V2203	Kubota V3600	Kubota V3600	Kubota V3600	Kubota V3600	Mitsubishi S6S-T	Mitsubishi S6S-T	Mitsubishi S6S-T	Mitsubishi S6S-T	Mitsubishi S6S-T	Mitsubishi S6S-T	Mitsubishi S6S-T
• Rated power	30,8 kW / 2400 rpm	30,8 kW / 2400 rpm	30,8 kW / 2400 rpm	48,8 kW / 2300 rpm	48,8 kW / 2300 rpm	48,8 kW / 2300 rpm	48,8 kW / 2300 rpm	67,7 kW / 2300 rpm	67,7 kW / 2300 rpm	67,7 kW / 2300 rpm	67,7 kW / 2300 rpm	67,7 kW / 2300 rpm	67,7 kW / 2300 rpm	67,7 kW / 2300 rpm
• Travel speed (unloaded)	19,5 km/hr (12,1 mph)	19,5 km/hr (12,1 mph)	19,5 km/hr (12,1 mph)	18,8 km/hr (11,7 mph)	18,8 km/hr (11,7 mph)	19,7 km/hr (12,2 mph)	19,7 km/hr (12,2 mph)	27,1 km/hr (16,8 mph)	26,1 km/hr (16,2 mph)	26,1 km/hr (16,2 mph)	26,0 km/hr (16,1 mph)	35,5 km/hr (22,1 mph)	35,4 km/hr (22,0 mph)	35,2 km/hr (21,9 mph)



LPG FORKLIFTS



	80D-7	110D-7E	130D-7E	140D-7E	160D-7E	15L-7	18L-7	20LA-7	20L-7	25L-7	30L-7
• Load capacity	8000 kg (16000 lb)	11000 kg (22000 lb)	13000 kg (26000 lb)	14000 kg (28000 lb)	16000 kg (32000 lb)	1500 kg (3000 lb)	1750 kg (3500 lb)	2000 kg (4000 lb)	2000 kg (4000 lb)	2500 kg (5000 lb)	3000 kg (6000 lb)
• Load center	600 mm (23,6 in)	600 mm (23,6 in)	600 mm (23,6 in)	600 mm (23,6 in)	600 mm (23,6 in)	500 mm (19,7 in)	500 mm (19,7 in)	500 mm (19,7 in)	500 mm (19,7 in)	500 mm (19,7 in)	500 mm (19,7 in)
• Lifting height (max.)	6070 mm (239,0 in)	7000 mm (275,6 in)	7000 mm (275,6 in)	7000 mm (275,6 in)	7000 mm (275,6 in)	7035 mm (277,0 in)	7035 mm (277,0 in)	7035 mm (277,0 in)	7000 mm (275,6 in)	7000 mm (275,6 in)	7000 mm (275,6 in)
• Engine	Mitsubishi S6S-DT	Cummins QSB6.7	Cummins QSB6.7	Cummins QSB6.7	Cummins QSB6.7	HMC Beta	HMC Beta	HMC Beta	HMC Beta	HMC Beta	HMC Beta
• Rated power	64,7 kW / 2200 rpm	119 kW / 2200 rpm	119 kW / 2200 rpm	119 kW / 2200 rpm	119 kW / 2200 rpm	37 kW / 2450 rpm	37 kW / 2450 rpm	37 kW / 2450 rpm	37 kW / 2450 rpm	37 kW / 2450 rpm	37 kW / 2450 rpm
• Travel speed (unloaded)	32,7 km/hr (20,3 mph)	33,6 km/hr (20,9 mph)	33,6 km/hr (20,9 mph)	33,6 km/hr (20,9 mph)	33,6 km/hr (20,9 mph)	20,7 km/hr (12,9 mph)	20,7 km/hr (12,9 mph)	20,7 km/hr (12,9 mph)	18,1 km/hr (11,2 mph)	18,1 km/hr (11,2 mph)	19,1 km/hr (11,9 mph)



BATTERY FORKLIFTS



	35L-7	40L-7	45L-7	15BT-7	18BT-7	20BT-7	16B-7	18B-7	20B-7	22B-7	25B-7	30B-7	32B-7
• Load capacity	3500 kg (7000 lb)	4000 kg (8000 lb)	4500 kg (9000 lb)	1500 kg (3000 lb)	1800 kg (3600 lb)	2000 kg (4000 lb)	1600 kg (3200 lb)	1750 kg (3500 lb)	2000 kg (4000 lb)	2200 kg (4400 lb)	2500 kg (5000 lb)	3000 kg (6000 lb)	3200 kg (6400 lb)
• Load center	600 mm (23,6 in)	600 mm (23,6 in)	600 mm (23,6 in)	500 mm (19,7 in)	500 mm (19,7 in)	500 mm (19,7 in)	500 mm (19,7 in)	500 mm (19,7 in)	500 mm (19,7 in)	500 mm (19,7 in)	500 mm (19,7 in)	500 mm (19,7 in)	500 mm (19,7 in)
• Lifting height (max.)	6030 mm (237,4 in)	6030 mm (237,4 in)	6030 mm (237,4 in)	7035 mm (277,0 in)	7035 mm (277,0 in)	7040 mm (277 in)	7035 mm (277,0 in)	7035 mm (277,0 in)	7040 mm (277 in)	6500 mm (255,9 in)	6500 mm (255,9 in)	6500 mm (255,9 in)	6500 mm (255,9 in)
• Engine	GM 4.3L	GM 4.3L	GM 4.3L	1570 mm (61,8 in)	1645 mm (64,8 in)	1685 mm (66,3 in)	1685 mm (66,3 in)	1770 mm (69,7 in)	1780 mm (70,1 in)	1865 mm (73,4 in)	1900 mm (74,8 in)	2120 mm (83,5 in)	2120 mm (83,5 in)
• Rated power	67,7 kW / 2300 rpm	67,7 kW / 2300 rpm	67,7 kW / 2300 rpm	48 V / 505 Ah	48 V / 585 Ah	48 V / 585 Ah	48 V / 505 Ah	48 V / 585 Ah	48 V / 585 Ah	48 V / 660 Ah	48 V / 715 Ah	48 V / 740 Ah	48 V / 740 Ah
• Travel speed (unloaded)	24,6 km/hr (15,3 mph)	23,2 km/hr (14,4 mph)	23,2 km/hr (14,4 mph)	17 km/hr (10,6 mph)	17 km/hr (10,6 mph)	17 km/hr (10,6 mph)	17 km/hr (10,6 mph)	17 km/hr (10,6 mph)	17 km/hr (10,6 mph)	18 km/hr (11,2 mph)	18 km/hr (11,2 mph)	18 km/hr (11,2 mph)	18 km/hr (11,2 mph)



REACH TRUCKS



	22BHA-7	25BHA-7	30BHA-7	35B-7	40B-7	45B-7	50B-7	10BR-7	13BR-7	14BR-7	15BR-7	18BR-7	20BR-7	25BR-7	14BRJ-7	16BRJ-7	20BRJ-7	25BRJ-7
• Load capacity	2200 kg (4400 lb)	2500 kg (5000 lb)	3000 kg (6000 lb)	3500 kg (7000 lb)	4000 kg (8000 lb)	4500 kg (9000 lb)	4990 kg (9980 lb)	1000 kg (2000 lb)	1250 kg (2500 lb)	1350 kg (2700 lb)	1500 kg (3000 lb)	1800 kg (3600 lb)	2000 kg (4000 lb)	2500 kg (5000 lb)	1400 kg (2800 lb)	1600 kg (3200 lb)	2000 kg (4000 lb)	2500 kg (5000 lb)
• Load center	500 mm (19,7 in)	500 mm (19,7 in)	500 mm (19,7 in)	500 mm (19,7 in)	500 mm (19,7 in)	500 mm (19,7 in)	500 mm (19,7 in)	500 mm (19,7 in)	500 mm (19,7 in)	500 mm (19,7 in)	500 mm (19,7 in)	500 mm (19,7 in)	500 mm (19,7 in)	500 mm (19,7 in)	600 mm (23,6 in)	600 mm (23,6 in)	600 mm (23,6 in)	600 mm (23,6 in)
• Lifting height (max.)	6500 mm (255,9 in)	6500 mm (255,9 in)	6500 mm (255,9 in)	6030 mm (237,4 in)	6030 mm (237,4 in)	6030 mm (237,4 in)	5962 mm (234,7 in)	7035 mm (277 in)	7035 mm (277 in)	7035 mm (277 in)	7035 mm (277 in)	7035 mm (277 in)	7005 mm (275,8 in)	7005 mm (275,8 in)	10501 mm (413,4 in)	10501 mm (413,4 in)	12007 mm (472,7 in)	12007 mm (472,7 in)
• Turning radius	1970 mm (77,6 in)	2030 mm (79,9 in)	2170 mm (85,4 in)	2460 mm (96,9 in)	2615 mm (103,0 in)	2660 mm (104,7 in)	2705 mm (106,5 in)	1425 mm (56,1 in)	1460 mm (57,5 in)	1545 mm (60,8 in)	1605 mm (63,2 in)	1775 mm (70,0 in)	1790 mm (70,5 in)	1985 mm (78,2 in)	1625 mm (64,0 in)	1675 mm (65,9 in)	1735 mm (68,3 in)	1885 mm (74,2 in)
• Battery Capacity	80 V / 500 Ah	80 V / 600 Ah	80 V / 600 Ah	80 V / 600 Ah	80 V / 700 Ah	80 V / 700 Ah	80 V / 700 Ah	48 V / 225 Ah	48 V / 225 Ah	48 V / 230 Ah	48 V / 280 Ah	48 V / 300 Ah	48 V / 335 Ah	48 V / 335 Ah	48 V / 420 Ah	48 V / 420 Ah	48 V / 560 Ah	48 V / 560 Ah
• Travel speed (unloaded)	19 km/hr (11,8 mph)	19 km/hr (11,8 mph)	19 km/hr (11,8 mph)	18 km/hr (11,2 mph)	18 km/hr (11,2 mph)	18 km/hr (11,2 mph)	18 km/hr (11,2 mph)	11,5 km/hr (7,2 mph)	11,5 km/hr (7,2 mph)	11,5 km/hr (7,2 mph)	11,5 km/hr (7,2 mph)	11,5 km/hr (7,2 mph)	11,5 km/hr (7,2 mph)	11,5 km/hr (7,2 mph)	14 km/hr (8,7 mph)	14 km/hr (8,7 mph)	14 km/hr (8,7 mph)	14 km/hr (8,7 mph)